

175 R8 Antiabrasion Twin



MEDIUM
PRESSURE

HIGH
PRESSURE

CONSTANT
PRESSURE

VERY HIGH
PRESSURE

Part No.	Hose size			ID		OD		WP		BP		Safety factor	Bend radius		Weight		Ferrule part no.	
	dash	inch	DN	mm	inch	mm	inch	bar	psi	bar	psi		mm	inch	g/m	lbs/ft	carbon	stainless
1750	-2	1/8"	4	4,00	0,157	8,00	0,315	420	6000	1680	24000	4:1	25	0,98	90	0,060	SAB101	SAB801
1751	-3	3/16"	5	5,00	0,197	8,90	0,350	350	5000	1400	20000	4:1	30	1,18	100	0,068	SAB111	SAB811
1752	-4	1/4"	6	6,50	0,256	11,50	0,453	350	5000	1400	20000	4:1	50	1,97	170	0,114	SAB121	SAB821
1753	-5	5/16"	8	8,10	0,319	13,40	0,528	300	4300	1200	17200	4:1	55	2,17	210	0,141	SAB131	SAB831
1754	-6	3/8"	10	9,70	0,382	15,50	0,610	280	4000	1120	16000	4:1	60	2,36	270	0,181	SAB141	SAB841
1755	-8	1/2"	12	13,00	0,512	19,90	0,783	245	3500	980	14000	4:1	80	3,15	400	0,269	SAB151	SAB851
1756	-10	5/8"	16	16,30	0,642	23,40	0,921	200	2900	800	11600	4:1	125	4,92	500	0,336	SAB161	SAB861
1757	-12	3/4"	20	19,50	0,768	26,90	1,059	165	2300	660	9200	4:1	150	5,91	640	0,430	SAB171	SAB871
1758	-16	1"	25	25,90	1,020	34,20	1,346	140	2000	560	8000	4:1	200	7,87	870	0,585	SAB181	SAB881

SPECIALITIES

OFF SHORE
MASTER

MICRO BORE

TWIN HOSES

082 2SB Two Steel Braids Antiabrasion Twin



Part No.	Hose size			ID		OD		WP		BP		Safety factor	Bend radius		Weight		Ferrule part no.	
	dash	inch	DN	mm	inch	mm	inch	bar	psi	bar	psi		mm	inch	g/m	lbs/ft	carbon	stainless
0822	-4	1/4"	6	6,40	0,252	12,80	0,504	400	5800	1600	23200	4:1	40	1,57	490	0,329	SAC121	SAC821
0823	-5	5/16"	8	8,10	0,319	14,80	0,583	400	5800	1600	23200	4:1	50	1,97	630	0,423	SAC131	SAC831
0824	-6	3/8"	10	9,80	0,386	16,80	0,661	330	4700	1320	18800	4:1	65	2,56	750	0,504	SAC141	SAC841
0825	-8	1/2"	12	13,00	0,512	20,20	0,795	260	3700	1040	14800	4:1	85	3,35	900	0,605	SAC151	SAC851
0826	-10	5/8"	16	16,30	0,642	23,50	0,925	220	3100	880	12400	4:1	115	4,53	1120	0,753	SAC161	SAC861
0827	-12	3/4"	20	19,50	0,768	27,50	1,083	150	2100	600	8400	4:1	170	6,69	1430	0,961	SAC171	SAC871