




Overview fitting series 56 - stainless steel

Metric fittings

CA Metric female swivel 24° with O-ring Light series – Metric swivel nut – ISO 12151-2 	CF Metric female swivel 24° with O-ring 90° elbow – Light series – Metric swivel nut – ISO 12151-2 
---	--

1CA56 – Metric female swivel 24° with O-ring

Light series – Metric swivel nut – ISO 12151-2




Part No. #	DN size mm inch				Connection type		A mm	B mm	J mm	Max. WP MPa
					Thread size	Tube OD mm				
										
1CA56-6-3C	5	-03	4.8	3/16	M12x1.5	6	39.6	21.9	14	31.5
1CA56-8-4C	6	-04	6.4	1/4	M14x1.5	8	47.1	22.6	17	42.5
1CA56-10-5C	8	-05	7.9	5/16	M16x1.5	10	47.9	22.1	19	40.0
1CA56-12-6C	10	-06	9.5	3/8	M18x1.5	12	47.6	22.4	22	35.0
1CA56-15-8C	12	-08	12.7	1/2	M22x1.5	15	53.3	24.9	27	31.5

Fittings with standard O-ring seals can be used for temperatures from -35 °C up to +100 °C.

1CF56 – Metric female swivel 24° with O-ring

90° elbow – Light series – Metric swivel nut – ISO 12151-2



Part No. #	DN size mm inch				Connection type		A mm	B mm	E mm	J mm	Max. WP MPa
	DN	size	mm	inch	Thread size	Tube OD mm					
											
1CF56-6-3C	5	-03	4.8	3/16	M12x1.5	6	48.0	30.3	30.0	14	31.5
1CF56-8-4C	6	-04	6.4	1/4	M14x1.5	8	55.0	30.0	28.5	17	42.5
1CF56-10-5C	8	-05	7.9	5/16	M16x1.5	10	66.0	40.0	29.0	19	40.0
1CF56-12-6C	10	-06	9.5	3/8	M18x1.5	12	63.0	38.0	35.0	22	35.0
1CF56-15-8C	12	-08	12.7	1/2	M22x1.5	15	68.0	39.6	42.6	27	31.5

Fittings with standard O-ring seals can be used for temperatures from -35 °C up to +100 °C.

Hose types to be used with fitting series 56 (check individual sizes in detail – CAT4460)

56 550H / 540N / 560 / 510A / 518C / 53DM / 55LT / 2040N / 2040H / 520N / 528N / 580N / 588N / 590